

背光光源 | BL系列 |



高亮度背光源，大幅提高了光源的均勻性和強度。背光源主要採用背式照明方式，可輔助影像辨識系統檢驗間接照明與定位各種透明及非透明被測物，或輪廓尺寸檢驗。

產品特徵：

- ◆ 高密度、高亮度、光線更加明亮
- ◆ 多尺寸、多顏色皆可客製
- ◆ 更好的均勻性

應用：

各類孔穴檢查、產品對位檢查、外型尺寸量測

型號選擇說明

CHD-BL-□□△△○
寬度 長度 顏色

產品型號規格

型號	發光色	功率(W)	輸入電壓(V)	輸出電流(mA)	尺寸圖
CHD-BL2320	 IR850/IR940 (IR光)	1.2	12V / 24V	100 / 50	1
CHD-BL2525	 IR850/IR940 (IR光)	1.2	12V / 24V	100 / 50	2
CHD-BL3130	 IR850/IR940 (IR光)	2.3	12V / 24V	192 / 96	3
CHD-BL4040	 IR850/IR940 (IR光)	1.8	12V / 24V	150 / 75	4
CHD-BL4845	 IR850/IR940 (IR光)	3.5	12V / 24V	292 / 146	5
CHD-BL5050	 IR850/IR940 (IR光)	3.5	12V / 24V	292 / 146	6
CHD-BL6030	 IR850/IR940 (IR光)	4.6	12V / 24V	383 / 192	7
CHD-BL6060	 IR850/IR940 (IR光)	10.8	12V / 24V	900 / 450	8
CHD-BL7566	 IR850/IR940 (IR光)	14.4	12V / 24V	1.2A / 600	9
CHD-BL7575	 IR850/IR940 (IR光)	14.4	12V / 24V	1.2A / 600	10
CHD-BL9060	 IR850/IR940 (IR光)	20.7	12V / 24V	1.7A / 862	11
CHD-BL9090	 IR850/IR940 (IR光)	20.7	12V / 24V	1.7A / 863	12
CHD-BL10050	 IR850/IR940 (IR光)	14.8	12V / 24V	1.2A / 616	13
CHD-BL10060	 IR850/IR940 (IR光)	8.6	12V / 24V	717 / 358	14
CHD-BL100100	 IR850/IR940 (IR光)	14.4	12V / 24V	1.2A / 600	15
CHD-BL10535	 IR850/IR940 (IR光)	9.4	12V / 24V	783 / 392	16
CHD-BL12060	 IR850/IR940 (IR光)	8.4	12V / 24V	700 / 350	17

產品型號規格

型號	發光色	功率(W)	輸入電壓(V)	輸出電流(mA)	尺寸圖
CHD-BL12090	 IR850/IR940 (IR光)	8.4	12V / 24V	700 / 350	18
CHD-BL120120	 IR850/IR940 (IR光)	46.6	12V / 24V	3.8A / 2A	19
CHD-BL15050	 IR850/IR940 (IR光)	15.3	12V / 24V	1.3A / 638	20
CHD-BL20050	 IR850/IR940 (IR光)	20.4	12V / 24V	1.7A / 850	21
CHD-BL31535	 IR850/IR940 (IR光)	28.2	12V / 24V	2.4A / 1.2A	22
CHD-BL42035	 IR850/IR940 (IR光)	37.6	12V / 24V	3.1A / 1.6A	23

光源尺寸圖



